



US005861773A

United States Patent [19]

Meyer

[11] Patent Number: 5,861,773

[45] Date of Patent: Jan. 19, 1999

[54] CIRCUIT FOR DETECTING THE LOCKED
CONDITION OF PSK OR QAM

[75] Inventor: Jacques Meyer, Corenc, France

[73] Assignee: SGS-Thomson Microelectronics S.A.,
Saint Genis, France

[21] Appl. No.: 982,979

[22] Filed: Dec. 2, 1997

Related U.S. Application Data

[63] Continuation of Ser. No. 675,632, Jul. 1, 1996, Pat. No.
5,703,526.

[30] Foreign Application Priority Data

Jul. 6, 1995 [FR] France 95 08401

[51] Int. Cl.⁶ H04L 27/22[52] U.S. Cl. 329/304; 329/308; 331/DIG. 2;
375/327; 375/329[58] Field of Search 329/304, 308,
329/309; 331/DIG. 2; 375/326; 327; 328;
329

[56] References Cited

U.S. PATENT DOCUMENTS

4,057,762 11/1977 Namiki 375/376
4,736,386 4/1988 Nichols 375/2244,853,642 8/1989 Otani et al. 329/306
4,870,382 9/1989 Keate et al. 331/4
4,958,360 9/1990 Sari 375/344
4,987,375 1/1991 Wu et al. 329/309
5,121,071 6/1992 Kelly et al. 329/307

FOREIGN PATENT DOCUMENTS

C-42 16 156 8/1993 Germany .

OTHER PUBLICATIONS

IEEE Transactions on Communication, vol. 30, No. 10, Oct.
1982 New York, US, pp. 2385-2390, Yoshio Matsuo & Junji
Namiki, "Carrier Recovery Systems For Arbitrarily Mapped
APK Signals".

Primary Examiner—Siegfried H. Grimm

Attorney, Agent, or Firm—Wolf, Greenfield & Sacks, P.C.

[57] ABSTRACT

A method for detecting a locked condition of a demodulator of at least one signal that may have discrete levels defining a constellation of nominal points in a plane. The method includes the steps of defining reference areas about the nominal points, a reference area being separated from another by a band or an angular sector crossing the origin of the constellation plane, and indicating a locked condition if the ratio of points occurring in the reference areas is above the probability for points to occur in the reference area, when the demodulator is wrongly adjusted.

6 Claims, 2 Drawing Sheets

